



SPECIFICATION SHEET

Specification of Mix Xylene			
	ASTM D-4052	TO BE REPORTED	gr/cm ³
		clear free of	
Appearance	Visual	haze/sediment	
Color Pt-Co Scale	ASTM D-1209	10 max	
Acid Wash Color	ASTM D-8486	6 max	
Acidity	ASTM D-847	no free acid	mgr NaOH/100ml
Copper Corrosion	ASTM D-849	No.1a	
H ₂ S & SO ₂ Content	ASTM D-853	free of H ₂ S/SO ₂	
	ASTM D-850	5 max	
I.B.P	ASTM D-850	137 min	
D.P	ASTM D-850	143 MAX	
PARA-XYLENE	ASTM D-2306	16.5 MIN	wt.%
ORTHO-XYLENE	ASTM D-2306	15 MIN	wt.%
ETHYL BENZENE	ASTM D-2306	18.5 max	wt.%
METHA XYLENE	ASTM D-2306	49 max	wt.%
BENZENE	ASTM D-2360	.005 max	wt.%
TOLUENE	ASTM D-2360	.04 max	wt.%
C ₉ AROMATICS	ASTM D-2360	.5 max	wt.%
	ASTM D-2360	0.05 max	wt.%
TOTAL SULFUR	UOP 727	1 max	wt.ppm
TOTAL CHLORIDES	IP-AK/81	1 max	wt.ppm
BROMINE INDEX	IP-129	20 max	mgr/100 gr